
webtest-casperjs Documentation

Release 0.1

Gael Pasgrimaud

February 03, 2017

1 Using casperjs to run tests	3
Python Module Index	5

Allow to run an external process to test your application

```
class webtest_casperjs.TestApp (app=None, url=None, timeout=30000, extra_environ=None, relative_to=None, **kwargs)
```

Run the test application in a separate thread to allow to access it via http

```
close ()
```

Close WSGI server if needed

```
webtest_casperjs.casperjs (*args, **kws)
```

A context manager to run a test with a `webtest.ext.TestApp`

Using casperjs to run tests

The js part:

```
var system = require('system');
var url = system.env['APPLICATION_URL'];

var casper = require('casper').create();
casper.start(url, function() {
    this.test.assertTitle('It Works!');
});

casper.run(function() {
    this.test.done();
    this.test.renderResults(true);
});
```

The python part:

```
def test_casperjs():
    app = webtest.TestApp(application)
    with webtest_casperjs.casperjs(app) as run:
        run('fixtures/test_casperjs.js')
```


W

`webtest_casperjs`, 3

C

[casperjs\(\)](#) (in module [webtest_casperjs](#)), 1
[close\(\)](#) ([webtest_casperjs.TestApp](#) method), 1

T

[TestApp](#) (class in [webtest_casperjs](#)), 1

W

[webtest_casperjs](#) (module), 1